

6 January 2006

RINEX: The Receiver Independent Exchange Format Version 2.11

Werner Gurtner
Astronomical Institute
University of Berne

Lou Estey
UNAVCO
Boulder, Co.

Contents:

- 0. Revision History
 - 0.1 Revision Summary
 - 0.2 First Revision
 - 0.3 Later Revisions
 - 0.4 Version 2.10 Modifications
 - 0.5 Version 2.10 Revisions
 - 0.6 Version 2.11 Modifications
- 1. THE PHILOSOPHY OF RINEX
- 2. GENERAL FORMAT DESCRIPTION
- 3. DEFINITION OF THE OBSERVABLES
- 4. THE EXCHANGE OF RINEX FILES:
- 5. RINEX VERSION 2 FEATURES
 - 5.1 Satellite Numbers:
 - 5.2 Order of the Header Records:
 - 5.3 Missing Items, Duration of the Validity of Values
 - 5.4 Event Flag Records
 - 5.5 Receiver Clock Offset
- 6. ADDITIONAL HINTS AND TIPS
 - 6.1 Version 1 / Version 2
 - 6.2 Leading Blanks in CHARACTER fields
 - 6.3 Variable-length Records
 - 6.4 Blank Fields
 - 6.5 2-Digit Years
 - 6.6 Fit Interval
 - 6.7 Satellite Health
 - 6.8 Transmission Time of Message (Navigation message file)
 - 6.9 Unknown / Undefined Observation Types and Header Records
- 7. RINEX UNDER ANTISPOOFING (AS)
- 8. GLONASS Extensions
 - 8.1 RINEX Observation File
 - 8.1.1 Time System Identifier
 - 8.1.2 Pseudorange Definition
 - 8.1.3 More Than 12 Satellites per Epoch
 - 8.2 RINEX Navigation Files for GLONASS
- 9. RINEX Extensions for Geostationary Satellites (GPS Signal Payloads)
 - 9.1 RINEX Observation Files for GEO Satellites
 - 9.2 RINEX Navigation Message Files for GEO Satellites

- 10. Version 2.11 Modifications
 - |
 - 10.1 Galileo and New GPS Observables
 - |
 - 10.1.1 New Observation Codes
 - |
 - 10.1.2 Wavelength Factors
 - |
 - 10.2 Clarifications in the GEO Navigation Message File
 - |
 - 10.3 New observables for RINEX met files
 - |

REFERENCES

APPENDIX: RINEX VERSION 2.10 FORMAT DEFINITIONS AND EXAMPLES

- A 1 GPS OBSERVATION DATA FILE - HEADER SECTION DESCRIPTION
- A 2 GPS OBSERVATION DATA FILE - DATA RECORD DESCRIPTION
- A 3 GPS NAVIGATION MESSAGE FILE - HEADER SECTION DESCRIPTION
- A 4 GPS NAVIGATION MESSAGE FILE - DATA RECORD DESCRIPTION
- A 5 METEOROLOGICAL DATA FILE - HEADER SECTION DESCRIPTION
- A 5 METEOROLOGICAL DATA FILE - DATA RECORD DESCRIPTION
- A 7 MIXED OBSERVATION DATA FILE - EXAMPLE
- |
- A 8 GPS NAVIGATION MESSAGE FILE - EXAMPLE
- A 9 METEOROLOGICAL DATA FILE - EXAMPLE
- A10 GLONASS NAVIGATION MESSAGE FILE - HEADER SECTION DESCRIPTION
- A11 GLONASS NAVIGATION MESSAGE FILE - DATA RECORD DESCRIPTION
- A12 GLONASS NAVIGATION MESSAGE FILE - EXAMPLE
- A13 GLONASS OBSERVATION FILE - EXAMPLE
- A14 MIXED GPS/GLONASS OBSERVATION FILE - EXAMPLE
- A15 GEOSTATIONARY NAVIGATION MESSAGE FILE - HEADER SECTION DESCRIPTION
- A16 GEOSTATIONARY NAVIGATION MESSAGE FILE - DATA RECORD DESCRIPTION
- A17 MIXED GPS/GEO OBSERVATION FILE - EXAMPLE
- A18 GEO NAVIGATION MESSAGE FILE - EXAMPLE

0. REVISION HISTORY

0.1 Revision Summary

First Revision, April 1993
 Clarification December 1993
 Doppler Definition: January 1994
 PR Clarification: October 1994
 Wlfact Clarification: February 1995
 Event Time Frame Clarification: May 1996
 Minor errors in the examples A7/A8: May 1996
 Naming convention for compressed met files; January 1997
 Continuation line clarifications: April 1997
 GLONASS Extensions: April 1997
 Met sensor description and position records: April 1997
 Wavelength factor clarifications: April 1997
 Error in example A12: CORR TO SYSTEM TIME, April 1997
 Redefinition of sv clock params in GLONASS Nav Mess Files: March 1998
 Naming conventions for compressed RINEX obs files: March 1998
 GPS week: No roll-over, continuous number: March 1998
 Error in compressed DOS file naming convention: July 1998
 Table A13 contained blank satellite identifiers: Sept 1998
 Discrepancy between Tables A5 and A9 removed: Sept 1998
 Phase data format overflow: Clarification: Oct 1998
 Message frame time Table A11: Clarification: Oct 1998
 RINEX Version 2.10 Modifications: July 1999
 Typo in paragraph 0.4 (epoch flag >1): Nov 1999
 Clarification regarding trailing blanks: Dec 1999
 Clarification regarding units of ZD,ZT, URA(GEO)

Clarification regarding time system identifier of GEO obs files
Clarification regarding time system identifier in TIME OF LAST record: Feb 2000
Addition of GEO examples: February 2000
Clarification of epoch field for event flag records: May 2000
Table A6: Typos in format definition of epoch: May 2000
Clarification of the GLONASS satellite identifier: June 2001
Clarification of the floating point exponent format: January 2002
RINEX Version 2.11 modifications: October 2004
|
Some clarifications in the GEO D-UTC A0,A1,T,W,S,U record November 2005
|
Wind, rain and hail observables in met files: December 2005
|
Unknown/undefined observation types and header records: December 2005
|
References to clock and SBAS RINEX files. Extended filenames: December 2005
|

0.2 First Revision

The first documentation of the RINEX Version 2 Format was published by W. Gurtner and G. Mader in the CSTG GPS Bulletin of September/October 1990. The main reason for a revision is the new treatment of antispoofting data by the RINEX format (see chapter 7). Chapter 4 gives a recommendation for data compression procedures, especially useful when large amounts of data are exchanged through computer networks. In Table A3 in the original paper the definition of the "PGM / RUN BY / DATE" navigation header record was missing, although the example showed it. The redefinition of AODE/AODC to IODE/IODC also asked for an update of the format description. For consistency reasons we also defined a Version 2 format for the Meteorological Data files (inclusion of a END OF HEADER record and an optional MARKER NUMBER record).

The slight modification (or rather the definition of a bit in the Loss of Lock Indicator unused so far) to flag AS data is so small a change that we decided to NOT increase the version number!

0.3 Later Revisions

* URA Clarification (10-Dec-93):

The user range accuracy in the Navigation Message File did not contain a definition of the units: There existed two ways of interpretation: Either the 4 bit value from the original message or the converted value in meters according to GPS ICD-200. In order to simplify the interpretation for the user of the RINEX files I propose the bits to be converted into meters prior to RINEX file creation.

* GLONASS Extensions:

In March 1997 a proposal for extensions to the current RINEX definitions based on experiences collected with GLONASS only and mixed GPS/GLONASS data files was circulated among several instrument manufacturers and software developers.

The results of the call for comments have been worked into this document. A separate document (glonass.txt) summarizes just the necessary extensions.

* A blank satellite identifier is allowed in pure GPS files only

* Met sensor description and position records were added to facilitate the

precise use of met values.

* Description and examples for wavelength factors and their temporary changes

(bit 1 of LLI) clarified.

* The RINEX documentation distributed in spring 1997 contained definitions for

the GLONASS satellite clock offset and drift with the intention to have them

defined identically to the GPS values. Unfortunately the GLONASS Interface Document consulted had a sign error in one of the formulae.

The values should be stored into the RINEX file as $-\text{TauN}$, $+\text{GammaN}$, $-\text{TauC}$.

The original definition asked for $-\text{TauN}$, $-\text{GammaN}$, $+\text{TauC}$. See paragraph 8.2.

To avoid problems with files created with the original definitions a real valued version number (2.01) has been introduced for GLONASS nav mess files.

* IGS decided to use the Hatanaka compression scheme for RINEX observation files. Below the corresponding RINEX file name conventions are included as recommendations. The DOS naming (extension .yyE) was wrongly set to .yyY in the March 1998 version of the document.

* GPS week: The GPS week number in all RINEX files is a continuous number not affected by the 1024 roll-over, it runs from 1023 over 1024 to 1025 etc.

* A discrepancy between the definition of the header line fields of met sensor

description and position in Table A5 and the example in Table A9 was removed.

The latter was correct.

* Clarification for phase data format overflows: Add or subtract a suitable number of cycles, set LLI flag.

* Clarification for the GLONASS satellite identifier: "Almanac number" was somewhat ambiguous. It has been replaced by "slot number" within the satellite constellation.

0.4 Version 2.10 Modifications

The modifications leading to Version 2.10 include:

- Fractional version number
- Zero padding of 2-digit year values (years 2000-2009 --> 00-09)
- Field length of time of first obs (1/10 microsecond resolution)
- Non-integer sampling rate (INTERVAL header record)
- Header records now allowed after all epoch flags >1
- Additional obs types in obs files: S1, S2 (raw signal strength values)
- Receiver clock offset header line to clarify applied corrections
- Default wavelength factor header line mandatory
- Inmarsat GPS payloads: New satellite system definition, new nav mess files
- Curve fit interval in GPS nav mess file
- Redefinition of SV health value in GPS nav mess file
- Additional obs types in met files (ZD, ZT)

0.5 Version 2.10 Revisions

* "Header records now allowed after all epoch flags >2" in paragraph 0.4 should read ">1"

* The original intention of the RINEX format was to allow for variable record

lengths of the ASCII files to minimize the file size. Empty fields or unknown values can either be represented by zeroes or blank space. Most RINEX converters removed trailing blank to further reduce the file size. The documentation was not clear enough to explicitly allow for this practice (paragraphs 2, 5.3, 9.1).

- * The time system identifier of GPS observations generated by GEO payloads defaults to GPS (explicitly stated now in paragraph 9.1)
- * The time system identifier in the TIME OF LAST OBS header record has to be identical to the one in the TIME OF FIRST OBS record
- * Clarification of Table A2 to be compatible with examples of Table A7: For event flags without significant epoch the epoch fields can be left blank.
Table A6: Format for epoch contained obvious errors
- * Clarification of the floating point exponent format in navigation message files (two digits, E,e,D,d letters)

0.6 Version 2.11

|

|

The modifications of 2.10 leading to Version 2.11 include:

|

|

- Definition of the Galileo satellite system code

|

- Definition of the code for Galileo System Time (GAL)

|

- Definition of the frequency numbers for Galileo and new GPS observables

|

- Observation code for L2C pseudorange (C2)

|

- Some clarifications in the GEO NAV Message files:

|

- Transmission time of message

|

- Health

|

- URA

|

- CORR TO SYSTEM TIME replaced by more general D-UTC A0,A1,T,W,S,U record

|

- Introduction of wind speed and direction, rain fall increment, hail indicator|

- Recommendation regarding unknown/undefined observation types and header

|

records

|

- Recommendations for extended filenames for high-rate observation files

|

1. THE PHILOSOPHY OF RINEX

The first proposal for the "Receiver Independent Exchange Format" RINEX has been developed by the Astronomical Institute of the University of Berne for the easy exchange of the GPS data to be collected during the large European GPS campaign EUREF 89, which involved more than 60 GPS receivers of 4 different manufacturers. The governing aspect during the development was the following fact:

Most geodetic processing software for GPS data use a well-defined set of

observables:

- the carrier-phase measurement at one or both carriers (actually being a measurement on the beat frequency between the received carrier of the satellite signal and a receiver-generated reference frequency).
- the pseudorange (code) measurement, equivalent to the difference of the time of reception (expressed in the time frame of the receiver) and the time of transmission (expressed in the time frame of the satellite) of a distinct satellite signal.
- the observation time being the reading of the receiver clock at the instant of validity of the carrier-phase and/or the code measurements.

Usually the software assumes that the observation time is valid for both the phase AND the code measurements, AND for all satellites observed.

Consequently all these programs do not need most of the information that is usually stored by the receivers: They need phase, code, and time in the above mentioned definitions, and some station-related information like station name, antenna height, etc.

2. GENERAL FORMAT DESCRIPTION

Currently the format consists of seven ASCII file types:

1. Observation Data File
2. Navigation Message File
3. Meteorological Data File
4. GLONASS Navigation Message File
5. GEO Navigation Message File
6. Satellite and Receiver Clock Data File
7. SBAS Broadcast Data File

The format definition of the clock files has been published in 1998 in a separate document by Jim Ray and Werner Gurtner, available at the IGS Central Bureau Information System:

ftp://igs.cb.jpl.nasa.gov/igs.cb/data/format/rinex_clock.txt

The format definition of the Space-based augmentation system (SBAS) broadcast data file has been published in 2004 by Norbert Suard, Werner Gurtner and Lou

Estey, available at the IGS Central Bureau Information System:

ftp://igs.cb.jpl.nasa.gov/igs.cb/data/format/geo_sbas.txt

Each file type consists of a header section and a data section. The header section contains global information for the entire file and is placed at the beginning of the file. The header section contains header labels in columns 61-80 for each line contained in the header section. These labels are mandatory and must appear exactly as given in these descriptions and examples.

The format has been optimized for minimum space requirements independent from the number of different observation types of a specific receiver by indicating in the header the types of observations to be stored. In computer systems allowing variable record lengths the observation records may be kept as short as possible. Trailing blanks can be removed from the records. The maximum record length is 80 bytes per record.

Each Observation file and each Meteorological Data file basically contain the data from one site and one session. RINEX Version 2 also allows to include observation data from more than one site subsequently occupied by a roving receiver in rapid static or kinematic applications. Although Version 2 allows to insert header records into the data field we do not recommend to

concatenate data of more than one receiver (or antenna) into the same file, even if the data do not overlap in time.

If data from more than one receiver has to be exchanged it would not be economical to include the identical satellite messages collected by the different receivers several times. Therefore the Navigation Message File from one receiver may be exchanged or a composite Navigation Message File created containing non-redundant information from several receivers in order to make the most complete file.

The format of the data records of the RINEX Version 1 Navigation Message file is identical to the former NGS exchange format.

The actual format descriptions as well as examples are given in the Tables at the end of the paper.

3. DEFINITION OF THE OBSERVABLES

GPS observables include three fundamental quantities that need to be defined:

Time, Phase, and Range.

TIME:

The time of the measurement is the receiver time of the received signals. It is identical for the phase and range measurements and is identical for all satellites observed at that epoch. It is expressed in GPS time (not Universal Time).

PSEUDO-RANGE:

The pseudo-range (PR) is the distance from the receiver antenna to the satellite antenna including receiver and satellite clock offsets (and other biases, such as atmospheric delays):

$$\text{PR} = \text{distance} + c * (\text{receiver clock offset} - \text{satellite clock offset} + \text{other biases})$$

so that the pseudo-range reflects the actual behavior of the receiver and satellite clocks. The pseudo-range is stored in units of meters.

See also clarifications for pseudoranges in mixed GPS/GLONASS files in chapter 8.1.

PHASE:

The phase is the carrier-phase measured in whole cycles. The half-cycles measured by squaring-type receivers must be converted to whole cycles and flagged by the wavelength factor in the header section (GPS only).

The phase changes in the same sense as the range (negative doppler). The phase observations between epochs must be connected by including the integer number of cycles. The phase observations will not contain any systematic drifts from intentional offsets of the reference oscillators.

The observables are not corrected for external effects like atmospheric refraction, satellite clock offsets, etc.

If the receiver or the converter software adjusts the measurements using the real-time-derived receiver clock offsets $dT(r)$, the consistency of the 3 quantities phase / pseudo-range / epoch must be maintained, i.e. the receiver clock correction should be applied to all 3 observables:

```

Time(corr) = Time(r) - dT(r)
PR(corr)   = PR(r)   - dT(r)*c
phase(corr) = phase(r) - dT(r)*freq

```

DOPPLER:

The sign of the doppler shift as additional observable is defined as usual:
Positive for approaching satellites.

4. THE EXCHANGE OF RINEX FILES:

We recommend using the following naming convention for RINEX files:

ssssdddf.yyt

```

|
| | | | |
| | | | | +-- t: file type:
| | | | |   O: Observation file
| | | | |   N: GPS Navigation file
| | | | |   M: Meteorological data file
| | | | |   G: GLONASS Navigation file
| | | | |   L: Future Galileo Navigation file
|
| | | | |
| | | | |   H: Geostationary GPS payload nav mess file
| | | | |   B: Geo SBAS broadcast data file
| | | | |       (separate documentation)
| | | | |   C: Clock file (separate documentation)
| | | | |   S: Summary file (used e.g., by IGS, not a standard!)
|
| | | | |
| | | | | +--- yy: two-digit year
| | | | |
| | | | | +----- f: file sequence number/character within day
| | | | |   daily file: f = 0
| | | | |   hourly files:
| | | | |   f = a: 1st hour 00h-01h; f = b: 2nd hour 01h-02h;
... ; |
| | | | |   f = x: 24th hour 23h-24h
|
| | | | |
| | | | | +----- ddd: day of the year of first record
| | | | |
| | | | | +----- ssss: 4-character station name designator

```

For 15-minutes high-rate tracking data we recommend the following extended
filenames:

ssssdddhmm.yyo

```

|
| | | | |
| | | | | +- o: observation file
| | | | |
| | | | | +--- yy: two-digit year
| | | | |
| | | | |

```



```

| | | +----- mm: starting minute within the hour (00, 15, 30, 45)
| | |
| | | +----- h: character for the n-th hour in the day
| | |           (a= 1st hour: 00h-01h, b= 2nd hour: 1h to 2h,...,
| | |           x=24th hour: 23h-24h. 0= one-day file)
| | |
| | | +----- ddd: day of the year
| | |
| | | +----- ssss: 4-character ID for the LEO receiver/antenna
|

```

When data transmission times or storage volumes are critical we recommend compressing the files prior to storage or transmission using the UNIX "compress" und "uncompress" programs. Compatible routines are available on VAX/VMS and PC/DOS systems, as well.

Proposed file name extensions for the compressed files:

File Types	All platforms		
	UNIX	VMS	DOS
	uncompressed	compressed	
Obs Files	.yyO	.yyO.Z	.yyO_Z .yyY
Obs Files (Hatanaka compressed)	.yyD	.yyD.Z	.yyD_Z .yyE
GPS Nav Files	.yyN	.yyN.Z	.yyN_Z .yyX
GLONASS Nav File	.yyG	.yyG.Z	.yyG_Z .yyV
Galileo Nav File	.yyL	.yyL.Z	.yyL_Z .yyT
GEO Nav Files	.yyH	.yyH.Z	.yyH_Z .yyU
GEO SBAS Broadcast Files (sep. doc.)	.yyB	.yyB.Z	.yyB_Z .yyA
Met Data Files	.yyM	.yyM.Z	.yyM_Z .yyW
Clock Files (see sep.doc.)	.yyC	.yyC.Z	.yyC_Z .yyK

References for the Hatanaka compression scheme: See e.g.

- ftp://terras.gsi.go.jp/software
- IGSMails 1525,1686,1726,1763,1785,4967,4969,4975

5. RINEX VERSION 2 FEATURES

The following section contains features that have been introduced for RINEX Version 2:

5.1 Satellite Numbers:

Version 2 has been prepared to contain GLONASS or other satellite systems' observations. Therefore we have to be able to distinguish the satellites of the different systems: We precede the 2-digit satellite number with a system identifier.

```
snn          s:    satellite system identifier
                G or blank : GPS
                R          : GLONASS
                S          : Geostationary signal payload
                E          : Galileo

|

(GLONASS) | mn:    - PRN (GPS, Galileo), slot number
                - PRN-100 (GEO)
```

Note: G is mandatory in mixed GPS/GLONASS/Galileo files

(blank default modified in April 1997)

5.2 Order of the Header Records:

As the record descriptors in columns 61-80 are mandatory, the programs reading a RINEX Version 2 header are able to decode the header records with formats according to the record descriptor, provided the records have been first read into an internal buffer.

We therefore propose to allow free ordering of the header records, with the following exceptions:

- The "RINEX VERSION / TYPE" record must be the first record in a file
- The default "WAVELENGTH FACT L1/2" record must precede all records defining |
wavelength factors for individual satellites
- The "# OF SATELLITES" record (if present) should be immediately followed by the corresponding number of "PRN / # OF OBS" records. (These records may be handy for documentary purposes. However, since they may only be created after having read the whole raw data file we define them to be optional.

5.3 Missing Items, Duration of the Validity of Values

Items that are not known at the file creation time can be set to zero or blank or the respective record may be completely omitted. Consequently items of missing header records will be set to zero or blank by the program reading RINEX files. Trailing blanks may be truncated from the record.

Each value remains valid until changed by an additional header record.

5.4 Event Flag Records

The "number of satellites" also corresponds to the number of records of the same epoch followed. Therefore it may be used to skip the appropriate number of records if certain event flags are not to be evaluated in detail.

5.5 Receiver Clock Offset

A large number of users asked to optionally include a receiver-derived clock offset into the RINEX format. In order to remove uncertainties if the data (epoch, pseudorange, phase) have been previously corrected or not by the reported clock offset, RINEX Version 2.10 requests a clarifying (new) header record.

It would then be possible to reconstruct the original observations if necessary.

As the output format for the receiver-derived clock offset is limited to nanoseconds the offset should be rounded to the nearest nanosecond before it is used to correct the observables in order to guarantee correct reconstruction.

6. ADDITIONAL HINTS AND TIPS

6.1 Versions

Programs developed to read RINEX files have to verify the version number. Files of newer versions may look different even if they do not use any of the newer features

6.2 Leading Blanks in CHARACTER fields

We propose that routines to read RINEX Version 2 files automatically delete leading blanks in any CHARACTER input field. Routines creating RINEX Version 2 files should also left-justify all variables in the CHARACTER fields.

6.3 Variable-length Records

DOS, and other, files may have variable record lengths, so we recommend to first read each observation record into a 80-character blank string and decode the data afterwards. In variable length records, empty data fields at the end of a record may be missing, especially in the case of the optional receiver clock offset.

6.4 Blank Fields

In view of future modifications we recommend to carefully skip any fields currently defined to be blank (Format fields nX), because they may be assigned to new contents in future versions.

6.5 2-Digit Years

RINEX version 2 stores the years of data records with two digits only. The header of observation files contains a TIME OF FIRST OBS record with the full four-digit year, the GPS nav messages contain the GPS week numbers. From these two data items the unambiguous year can easily be reconstructed.

A hundred-year ambiguity occurs in the met data and GLONASS and GEO nav messages: Instead of introducing a new TIME OF FIRST OBS header line it is safe to stipulate that any two-digit years in RINEX Version 1 and Version 2.xx files are understood to represent

80-99: 1980-1999
00-79: 2000-2079

Full 4-digit year fields could then be defined by a future RINEX version 3.

6.6 Fit Interval

Bit 17 in word 10 of subframe 2 is a "fit interval" flag which indicates the curve-fit interval used by the GPS Control Segment in determining the ephemeris parameters, as follows (see ICD-GPS-200, 20.3.3.4.3.1):

0 = 4 hours
1 = greater than 4 hours.

Together with the IODC values and Table 20-XII the actual fit interval can be determined. The second value in the last record of each message shall contain the fit interval in hours determined using IODC, fit flag, and Table 20-XII, according to the Interface Document ICD-GPS-200.

6.7 Satellite Health

The health of the signal components (bits 18 to 22 of word three in subframe one) are now (Version 2.10) included into the health value reported in the second field of the sixth nav mess records.

A program reading RINEX files could easily decide if bit 17 only or all bits (17-22) have been written:

RINEX Value: 0 Health OK
RINEX Value: 1 Health not OK (bits 18-22 not stored)
RINEX Value: >32 Health not OK (bits 18-22 stored)

6.8 Transmission Time of Message (Navigation message file)

The transmission time of message can be shortly before midnight Saturday/Sunday, the TOE and TOC of the message already in the next week. As the reported week in the RINEX nav message (BROADCAST ORBIT - 5 record) goes with ToE (this is different from the GPS week in the original satellite message!), the transmission time of message should be reduced by 604800 (i.e., will become negative) to also refer to the same week.

6.9 Unknown / Undefined Observation Types and Header Records

|
|
| It is a good practice for a program reading RINEX files to make sure that it
| does not crash if it encounters unknown observation types or header records
| by properly skipping them and optionally reporting them to the user.
|

7. RINEX UNDER ANTISPOOFING (AS)

Some receivers generate code delay differences between the first and second frequency using cross-correlation techniques when AS is on and may recover the phase observations on L2 in full cycles. Using the C/A code delay on L1 and the observed difference it is possible to generate a code delay observation for the second frequency.

Other receivers recover P code observations by breaking down the Y code into P and W code.

Most of these observations may suffer from an increased noise level. In order to enable the postprocessing programs to take special actions, such AS-infected observations are flagged using bit number 2 of the Loss of Lock Indicators (i.e. their current values are increased by 4).

8. GLONASS Extensions

8.1 RINEX Observation File

8.1.1 Time System Identifier

The original RINEX Version 2 needed one major supplement, the explicit definition of the time system:

GLONASS is basically running on UTC (or, more precisely, GLONASS system time linked to UTC(SU)), i.e. the time tags are given in UTC and not GPS time. In order to remove possible misunderstandings and ambiguities, the header records "TIME OF FIRST OBS" and (if present) "TIME OF LAST OBS" in GLONASS and GPS observation files `_can_`, in mixed GLONASS/GPS observation files `_must_` contain a time system identifier defining the system that all time tags in the file are referring to: "GPS" to identify GPS time, "GLO" to identify the GLONASS UTC time system. Pure GPS files default to GPS and pure GLONASS files default to GLO.

Format definitions see Table A1.

Hence, the two possible time tags differ by the current number of leap seconds.

In order to have the current number of leap seconds available we recommend to include a LEAP SECOND line into the RINEX header.

If there are known non-integer biases between the "GPS receiver clock" and "GLONASS receiver clock" in the same receiver, they should be applied. In this case the respective code and phase observations have to be corrected, too ($c * \text{bias}$ if expressed in meters).

Unknown such biases will have to be solved for during the post processing

The small differences (modulo 1 second) between GLONASS system time, UTC(SU), UTC(USNO) and GPS system time have to be dealt with during the post-processing and not before the RINEX conversion. It may also be necessary to solve for remaining differences during the post-processing.

8.1.2 Pseudorange Definition

The pseudorange (code) measurement is defined to be equivalent to the difference of the time of reception (expressed in the time frame of the receiver) and the time of transmission (expressed in the time frame of the satellite) of a distinct satellite signal.

If a mixed-mode GPS/GLONASS receiver refers all pseudorange observations to one receiver clock only,

- the raw GLONASS pseudoranges will show the current number of leap seconds between GPS time and GLONASS time if the receiver clock is running in the GPS time frame
- the raw GPS pseudoranges will show the negative number of leap seconds

between GPS time and GLONASS time if the receiver clock is running in the GLONASS time frame

In order to avoid misunderstandings and to keep the code observations within the format fields, the pseudoranges must be corrected in this case as follows:

```
PR(GPS) := PR(GPS) + c * leap_seconds    if generated with a receiver clock
                                             running in the GLONASS time frame

PR(GLO) := PR(GLO) - c * leap_seconds    if generated with a receiver clock
                                             running in the GPS time frame
```

to remove the contributions of the leap seconds from the pseudoranges.

"leap_seconds" is the actual number of leap seconds between GPS and GLONASS (UTC) time, as broadcast in the GPS almanac and distributed in Circular T of BIPM.

8.1.3 More Than 12 Satellites per Epoch

The format of the epoch / satellite line in the observation record part of the RINEX Observation files has only been defined for up to 12 satellites per epoch. We explicitly define now the format of the continuation lines, see Table A2.

8.2 RINEX Navigation Files for GLONASS

As the GLONASS navigation message differs in contents from the GPS message too much, a special GLONASS navigation message file format has been defined.

The header section and the first data record (epoch, satellite clock information) is similar to the GPS navigation file. The following records contain the satellite position, velocity and acceleration, the clock and frequency biases as well as auxiliary information as health, satellite frequency (channel), age of the information.

The corrections of the satellite time to UTC are as follows:

```
GPS      : Tutc = Tsv - af0 - af1 *(Tsv-Toc) - ... - A0 - ... -
leap_sec
GLONASS: Tutc = Tsv + TauN - GammaN*(Tsv-Tb)          + TauC
```

*** In order to use the same sign conventions for the GLONASS corrections as in the GPS navigation files, the broadcast GLONASS values are stored as:
-TauN, +GammaN, -TauC.

The time tags in the GLONASS navigation files are given in UTC (i.e. not Moscow time or GPS time).

File naming convention: See above.

9. RINEX Extensions for Geostationary Satellites (GPS Signal Payloads)

With the implementation of GNSS programs, GPS-like ranging measurements can be performed on geostationary navigation payloads.

RINEX Version 2.10 defines the necessary extensions to handle such data in RINEX files for data exchange and postprocessing purposes.

9.1 RINEX Observation Files for GEO Satellites

A new satellite system identifier has been defined for the geostationary GPS signal payloads: "S", to be used in the RINEX VERSION / TYPE header line and in the satellite identifier 'snn', nn being the GEO PRN number minus 100.

e.g.: PRN = 120 --> 'snn' = "S20"

In mixed dual frequency GPS satellite / single frequency GEO payload observation files the fields for the second frequency observations of GEO satellites remain blank, are set to zero values or (if last in the record) can be truncated.

The time system identifier of GEO satellites generating GPS signals defaults to GPS time.

9.2 RINEX Navigation Message Files for GEO Satellites

As the GEO broadcast orbit format differs from the GPS message a special GEO navigation message file format has been defined which is nearly identical with the GLONASS nav mess file format.

The header section contains informations about the generating program, comments, and the difference between the GEO system time and UTC.

The first data record contains the epoch and satellite clock information, the following records contain the satellite position, velocity and acceleration and auxiliary information such as health, age of the data, etc.

The time tags in the GEO navigation files are given in the GPS time frame, i.e. not UTC.

The corrections of the satellite time to UTC are as follows:

$$\text{GEO} \quad : \quad \text{Tutc} = \text{Tsv} - \text{aGf0} - \text{aGf1} * (\text{Tsv} - \text{Toe}) - \text{W0} - \text{leap_sec}$$

W0 being the correction to transform the GEO system time to UTC. Toe, aGf0, aGf1 see below in the format definition tables.

The "Transmission Time of Message" (PRN / EPOCH / SV CLK header record) is expressed in GPS seconds of the week. It marks the beginning of the message transmission. It has to refer to the same GPS week as the "Epoch of Ephemerides". It has to be adjusted by - or + 604800 seconds, if necessary (which would make it lower than zero or larger than 604800, respectively). It is a redefinition of the Version 2.10 "Message frame time".

"Health" shall be defined as follows:

- Bits 0 to 3 equal to Health in Message Type 17 (MT17)
- bit 4 is set to 1 if MT17 health is unavailable
- bit 5 is set to 1 if the URA index is equal to 15

In the SBAS message definitions bit 3 of the health is currently marked as

| 'reserved'.
|

| In case of bit 4 set to 1, it is recommended to set bits 0,1,2,3 to 1,
| too. |

| "User Range Accuracy" (URA):
|

| The same convention for converting the URA index to meters is used as
| with GPS. Set URA = 32767 meters if URA index = 15.
|

| "IODN" (Issue Of Data Navigation)
|

| The IODN is defined as the 8 first bits after the message type 9,
| called IODN in RTCA DO229, Annex A and Annex B and called "spare" in Annex
| C. |

| The "CORR TO SYSTEM" TIME header record has been replaced by the more
| general |
| record "D-UTC A0,A1,T,W,S,U" in Version 2.11.
|

| 10. Version 2.11 Modifications |

| The main driver for version 2.11 was the easy inclusion of Galileo and new
| GPS |
| observables into the RINEX format. As these modifications are VERY MINOR (no
| changes in the actual formats) many RINEX readers will not have to be
| modified at all or to a small amount (accept version number 2.11), only.
|

| After the first introduction of the "GEO navigation message file" in Version
| 2.10 feedback from the SBAS community lead to a number of clarifications/
| redefinitions that were included in the Version 2.11 modifications.
|

| 10.1 Galileo and New GPS Observables |

| 10.1.1 New Observation Codes |

| In Version 2.10 only the observation codes for two frequencies were define

(Table A1).

The new codes for GPS L2C/L5 and Galileo codes are introduced as follows:

System	Freq.Band	Frequency	RINEX 2-character Code			
			Ps.Range	Carr.Phase	Doppler	Sign.Strength
GPS	L1	1575.42	C1,P1	L1	D1	S1
	L2	1227.60	C2,P2	L2	D2	S2
	L5	1176.45	C5	L5	D5	S5
Glonass	G1	$1602+k*9/16$	C1,P1	L1	D1	S1
	G2	$1246+k*7/16$	C2,P2	L2	D2	S2
Galileo	E2-L1-E1	1575.42	C1	L1	D1	S1
	E5a	1176.45	C5	L5	D5	S5
	E5b	1207.140	C7	L7	D7	S7
	E5a+b	1191.795	C8	L8	D8	S8
	E6	1278.75	C6	L6	D6	S6
SBAS	L1	1575.42	C1	L1	D1	S1
	L5	1176.45	C5	L5	D5	S5

The current two-character observation code does not easily allow a further refinement of the code to account for the different possibilities how to generate a specific observable, e.g., with respect to the underlying code (P,Y,M code in GPS) or the channels (I,Q, A,B,C in Galileo, I,Q in the new GPS L5 frequency, GPS L2C). The next RINEX version (3.0) will increase the length of the observation codes to allow a more detailed definition.

The definition of observations for Transit Doppler is obsolete and has been

removed from Version 2.11

10.1.2 Wavelength Factors

The WAVELENGTH FACT L1/2 header record defining the factor, the carrier wavelength has to be divided with for ambiguity resolution, has been introduced because of receivers generating GPS phase observations under antispoofing with one cycle corresponding to half the carrier wavelength only (squaring technique). Galileo observables will not be generated by squaring. We therefore define the WAVELENGTH FACT L1/2 header record to be valid for L1 and L2 GPS phase observables only. All wavelength factors default to 1. This header record can therefore be declared to be optional.

10.1.3 Code for Galileo Satellite System

Use "E" to indicate the Galileo Satellite System in the header of RINEX observation files.

10.1.4 Galileo System Time

Include GAL as Galileo System Time into TIME OF FIRST OBS and TIME OF LAST OBS header records.

10.2 Clarifications in the GEO Navigation Message File

The following clarifications/modifications were introduced (see chapter 9.2):

- Health word
- Issue of Data (Navigation) IODN
- Correction to system time
- Transmission time of message

10.3 New observables for RINEX met files

|
 Wind speed (ms), wind direction (from where the wind blows), and an
 |
 incremental rain fall value (1/10 mm): rain accumulation since the last
 |
 recording, hail indicator
 |

REFERENCES

Evans, A. (1989): "Summary of the Workshop on GPS Exchange Formats." Proceedings of the Fifth International Geodetic Symposium on Satellite Systems, pp. 917ff, Las Cruces.

Gurtner, W., G. Mader, D. Arthur (1989): "A Common Exchange Format for GPS Data." CSTG GPS Bulletin Vol.2 No.3, May/June 1989, National Geodetic Survey, Rockville.

Gurtner, W., G. Mader (1990): "The RINEX Format: Current Status, Future Developments." Proceedings of the Second International Symposium of Precise Positioning with the Global Positioning system, pp. 977ff, Ottawa.

Gurtner, W., G. Mader (1990): "Receiver Independent Exchange Format Version 2." CSTG GPS Bulletin Vol.3 No.3, Sept/Oct 1990, National Geodetic Survey, Rockville.

Gurtner, W. (1994): "RINEX: The Receiver-Independent Exchange Format." GPS World, Volume 5, Number 7, July 1994.

Gurtner, W. (2002): "RINEX: The Receiver Independent Exchange Format
 |
 Version 2.10". ftp://igsb.jpl.nasa.gov/igsb/data/format/rinex210.txt
 |

Ray, J., W. Gurtner (1999): "RINEX Extensions to Handle Clock Information".
 |
 ftp://igsb.jpl.nasa.gov/igsb/data/format/rinex_clock.txt
 |

Suard, N., W. Gurtner, L. Estey (2004): "Proposal for a new RINEX-type
 |
 Exchange File for GEO SBAS Broadcast Data".
 |
 ftp://igsb.jpl.nasa.gov/igsb/data/format/geo_sbas.txt
 |

Document RTCA DO 229, Appendix A
 |

APPENDIX: RINEX VERSION 2.11 FORMAT DEFINITIONS AND EXAMPLES

```

+-----+
--+
|
|                                     TABLE A1
|
|                               GNSS OBSERVATION DATA FILE - HEADER SECTION DESCRIPTION
|
+-----+-----+-----+
--+
|  HEADER LABEL  |  DESCRIPTION  |  FORMAT  |
|  (Columns 61-80)  |  |  |  |
|
+-----+-----+-----+

```

```

--+
|RINEX VERSION / TYPE | - Format version (2.11) | F9.2,11X,
| | | - File type ('O' for Observation Data) | A1,19X,
| | | - Satellite System: blank or 'G': GPS | A1,19X
| | | 'R': GLONASS |
| | | 'S': Geostationary |
| | | signal payload |
| | | 'E': Galileo |
| | | 'M': Mixed |
+-----+-----+-----+
--+
|PGM / RUN BY / DATE | - Name of program creating current file | A20,
| | | - Name of agency creating current file | A20,
| | | - Date of file creation | A20
+-----+-----+-----+
--+
*|COMMENT | Comment line(s) | A60
|*
+-----+-----+-----+
--+
|MARKER NAME | Name of antenna marker | A60
+-----+-----+-----+
--+
*|MARKER NUMBER | Number of antenna marker | A20
|*
+-----+-----+-----+
--+
|OBSERVER / AGENCY | Name of observer / agency | A20,A40
+-----+-----+-----+
--+
|REC # / TYPE / VERS | Receiver number, type, and version | 3A20
| | | (Version: e.g. Internal Software Version) |
+-----+-----+-----+
--+
|ANT # / TYPE | Antenna number and type | 2A20
+-----+-----+-----+
--+
|APPROX POSITION XYZ | Approximate marker position (WGS84) | 3F14.4
+-----+-----+-----+
--+
|ANTENNA: DELTA H/E/N| - Antenna height: Height of bottom | 3F14.4
| | | surface of antenna above marker |
| | | - Eccentricities of antenna center |
| | | relative to marker to the east |
| | | and north (all units in meters) |

```

--+		
* WAVELENGTH FACT L1/2	- Default wavelength factors for	
*	L1 and L2 (GPS only)	2I6,
	1: Full cycle ambiguities	
	2: Half cycle ambiguities (squaring)	
	0 (in L2): Single frequency instrument	
	- zero or blank	I6
	The wavelength factor record is optional	
	for GPS and obsolete for other systems.	
	Wavelength factors default to 1.	
	If the record exists it must precede any	
	satellite-specific records (see below).	

--+		
* WAVELENGTH FACT L1/2	- Wavelength factors for L1 and L2 (GPS)	2I6,
*	1: Full cycle ambiguities	
	2: Half cycle ambiguities (squaring)	
	0 (in L2): Single frequency instrument	
	- Number of satellites to follow in list	I6,
	for which these factors are valid.	
	- List of PRNs (satellite numbers with	
7(3X,A1,I2)	system identifier)	
	These optional satellite specific lines	
	may follow, if they identify a state	
	different from the default values.	
	Repeat record if necessary.	

--+		
# / TYPES OF OBSERV	- Number of different observation types	I6,
	stored in the file	
	- Observation types	
	- Observation code	9(4X,A1,
	- Frequency code	

A1)|||

|6X,9(4X,2A1)||

| If more than 9 observation types: |
| Use continuation line(s) |
| |
| The following observation types are |
| defined in RINEX Version 2.11: |
| |
| Observation code (use uppercase only): |
| C: Pseudorange GPS: C/A, L2C |
| Glonass: C/A |
| Galileo: All |
| P: Pseudorange GPS and Glonass: P code |
| L: Carrier phase |
| D: Doppler frequency |
| S: Raw signal strengths or SNR values |
| as given by the receiver for the |
| respective phase observations |
| |
| Frequency code |
| GPS Glonass Galileo SBAS |
| 1: L1 G1 E2-L1-E1 L1 |
| 2: L2 G2 -- -- |
| 5: L5 -- E5a L5 |
| 6: -- -- E6 -- |
| 7: -- -- E5b -- |
| 8: -- -- E5a+b -- |
| |
| Observations collected under Antispoofing |
| are converted to "L2" or "P2" and flagged |
| with bit 2 of loss of lock indicator |
| (see Table A2). |
| |
| Units : Phase : full cycles |
| Pseudorange : meters |

	Doppler	: Hz	
	SNR etc	: receiver-dependent	
	The sequence of the types in this record has to correspond to the sequence of the observations in the observation records		

--+	* INTERVAL	Observation interval in seconds	F10.3
	*		

--+	TIME OF FIRST OBS	- Time of first observation record	
5I6,F13.7,		(4-digit-year, month,day,hour,min,sec)	
		- Time system: GPS (=GPS time system)	5X,A3
		GLO (=UTC time system)	
		GAL (=Galileo System Time)	
		Compulsory in mixed GPS/GLONASS files	
		Defaults: GPS for pure GPS files	
		GLO for pure GLONASS files	
		GAL for pure Galileo files	

--+	* TIME OF LAST OBS	- Time of last observation record	
5I6,F13.7, *		(4-digit-year, month,day,hour,min,sec)	
		- Time system: Same value as in	5X,A3
		TIME OF FIRST OBS record	

--+	* RCV CLOCK OFFS APPL	Epoch, code, and phase are corrected by	I6
	*	applying the realtime-derived receiver	
		clock offset: 1=yes, 0=no; default: 0=no	
		Record required if clock offsets are	
		reported in the EPOCH/SAT records	

--+	* LEAP SECONDS	Number of leap seconds since 6-Jan-1980	I6
	*	Recommended for mixed files	

--+	* # OF SATELLITES	Number of satellites, for which	I6

*	observations are stored in the file	

--+		
* PRN / # OF OBS	PRN (sat.number), number of observations	
3X,A1,I2,9I6 *	for each observation type indicated	
	in the "# / TYPES OF OBSERV" - record.	
	If more than 9 observation types:	
	Use continuation line(s)	6X,9I6
	This record is (these records are)	
	repeated for each satellite present in	
	the data file	

--+		
END OF HEADER	Last record in the header section.	60X

--+		

Records marked with * are optional

TABLE A2		
GNSS OBSERVATION DATA FILE - DATA RECORD DESCRIPTION		

--+		
OBS. RECORD	DESCRIPTION	FORMAT

--+		
EPOCH/SAT	- Epoch :	
or	- year (2 digits, padded with 0 if necessary)	1X,I2.2,
EVENT FLAG	- month,day,hour,min,	
4(1X,I2),	- sec	F11.7,
	- Epoch flag 0: OK	2X,I1,
	1: power failure between	
	previous and current epoch	
	>1: Event flag	
	- Number of satellites in current epoch	I3,

If more than 5 observation types (=80 char):
continue observations in next record.

This record is (these records are) repeated for
each satellite given in EPOCH/SAT - record.

Observations:

Phase : Units in whole cycles of carrier

Code : Units in meters

Missing observations are written as 0.0

or blanks.

Phase values overflowing the fixed format F14.3
have to be clipped into the valid interval (e.g.
add or subtract 10^{*9}), set LLI indicator.

Loss of lock indicator (LLI). Range: 0-7

0 or blank: OK or not known

Bit 0 set : Lost lock between previous and
current observation: cycle slip
possible

Bit 1 set : Opposite wavelength factor to the
one defined for the satellite by a
previous WAVELENGTH FACT L1/2 line
or opposite to the default.

Valid for the current epoch only.

Bit 2 set : Observation under Antispoofing
(may suffer from increased noise)

Bits 0 and 1 for phase only.

Signal strength projected into interval 1-9:

	1: minimum possible signal strength	
	5: threshold for good S/N ratio	
	9: maximum possible signal strength	
	0 or blank: not known, don't care	

--+

--+

TABLE A3

GPS NAVIGATION MESSAGE FILE - HEADER SECTION DESCRIPTION

HEADER LABEL (Columns 61-80)	DESCRIPTION	FORMAT
---------------------------------	-------------	--------

--+

RINEX VERSION / TYPE	- Format version (2.10)	F9.2,11X,
	- File type ('N' for Navigation data)	A1,19X

--+

PGM / RUN BY / DATE	- Name of program creating current file	A20,
	- Name of agency creating current file	A20,
	- Date of file creation	A20

--+

* COMMENT	Comment line(s)	A60
-----------	-----------------	-----

--+

* ION ALPHA 2X,4D12.4 *	Ionosphere parameters A0-A3 of almanac (page 18 of subframe 4)	
------------------------------	---	--

--+

* ION BETA 2X,4D12.4 *	Ionosphere parameters B0-B3 of almanac	
-----------------------------	--	--

--+

* DELTA-UTC: A0,A1,T,W 3X,2D19.12, *	Almanac parameters to compute time in UTC (page 18 of subframe 4)	2I9
	A0,A1: terms of polynomial	
	T : reference time for UTC data	*)
	W : UTC reference week number.	
	Continuous number, not mod(1024)!	

--+

--+	* LEAP SECONDS	Delta time due to leap seconds	I6
	*		
+-----+			
--+	END OF HEADER	Last record in the header section.	60X
+-----+			
--+			

Records marked with * are optional

TABLE A4			
GPS NAVIGATION MESSAGE FILE - DATA RECORD DESCRIPTION			
OBS. RECORD	DESCRIPTION		FORMAT
PRN / EPOCH / SV CLK	- Satellite PRN number		I2,
	- Epoch: Toc - Time of Clock		
	year (2 digits, padded with 0		
	if necessary)		1X,I2.2,
	month		1X,I2,
	day		1X,I2,
	hour		1X,I2,
	minute		1X,I2,
	second		F5.1,
	- SV clock bias (seconds)		3D19.12
	- SV clock drift (sec/sec)		
	- SV clock drift rate (sec/sec2)		*)
+-----+			
BROADCAST ORBIT - 1	- IODE Issue of Data, Ephemeris		
3X,4D19.12	- Crs (meters)		
	- Delta n (radians/sec)		
	- M0 (radians)		
+-----+			
BROADCAST ORBIT - 2	- Cuc (radians)		
3X,4D19.12	- e Eccentricity		
	- Cus (radians)		

		- sqrt(A)	(sqrt(m))	

3X,4D19.12	BROADCAST ORBIT - 3	- Toe Time of Ephemeris		
			(sec of GPS week)	
		- Cic	(radians)	
		- OMEGA	(radians)	
		- CIS	(radians)	

3X,4D19.12	BROADCAST ORBIT - 4	- i0	(radians)	
		- Crc	(meters)	
		- omega	(radians)	
		- OMEGA DOT	(radians/sec)	

3X,4D19.12	BROADCAST ORBIT - 5	- IDOT	(radians/sec)	
		- Codes on L2 channel		
		- GPS Week # (to go with TOE)		
		Continuous number, not mod(1024)!		
		- L2 P data flag		

3X,4D19.12	BROADCAST ORBIT - 6	- SV accuracy	(meters)	
		- SV health	(bits 17-22 w 3 sf 1)	
		- TGD	(seconds)	
		- IODC Issue of Data, Clock		

3X,4D19.12	BROADCAST ORBIT - 7	- Transmission time of message	**)	
		(sec of GPS week, derived e.g.		
		from Z-count in Hand Over Word (HOW)		
		- Fit interval	(hours)	
		(see ICD-GPS-200, 20.3.4.4)		
		Zero if not known		
		- spare		
		- spare		

***) Adjust the Transmission time of message by -604800 to refer to the reported week, if necessary.

*) In order to account for the various compilers, E,e,D, and d are allowed letters between the fraction and exponent of all floating point numbers in the navigation message files.
Zero-padded two-digit exponents are required, however.

TABLE A5		
METEOROLOGICAL DATA FILE - HEADER SECTION DESCRIPTION		
HEADER LABEL (Columns 61-80)	DESCRIPTION	FORMAT
RINEX VERSION / TYPE	- Format version (2.11)	F9.2,11X,
	- File type ('M' for Meteorological Data)	A1,39X
PGM / RUN BY / DATE	- Name of program creating current file	A20,
	- Name of agency creating current file	A20,
	- Date of file creation	A20
* COMMENT	Comment line(s)	A60
* MARKER NAME	Station Name (preferably identical to MARKER NAME in the associated Observation File)	A60
* MARKER NUMBER	Station Number (preferably identical to MARKER NUMBER in the associated Observation File)	A20
# / TYPES OF OBSERV	- Number of different observation types stored in the file	I6,
	- Observation types	9(4X,A2)
	The following meteorological observation	

	types are defined in RINEX Version 2:	
	PR : Pressure (mbar)	
	TD : Dry temperature (deg Celsius)	
	HR : Relative humidity (percent)	
	ZW : Wet zenith path delay (mm)	
	(for WVR data)	
	ZD : Dry component of zenith path delay	
	(mm)	
	ZT : Total zenith path delay (mm)	
	WD : Wind azimuth (deg)	
	from where the wind blows	
	WS : Wind speed (m/s)	
	RI : "Rain increment" (1/10 mm): Rain	
	accumulation since last measurement	
	HI : Hail indicator: 1 = Hail detected	
	since last measurement	
	The sequence of the types in this record	
	must correspond to the sequence of the	
	measurements in the data records	
	If more than 9 observation types are	
	being used, use continuation lines with	
	format (6X,9(4X,A2))	
-----+-----		
---+	SENSOR MOD/TYPE/ACC	Description of the met sensor
		- Model (manufacturer)
		A20,
		- Type
		A20,6X,
		- Accuracy (same units as obs values)
F7.1,4X,		- Observation type
		A2,1X
		Record is repeated for each observation
		type found in # / TYPES OF OBSERV record

SENSOR POS XYZ/H	Approximate position of the met sensor	
	- Geocentric coordinates X,Y,Z (ITRF	3F14.4,
	- Ellipsoidal height H or WGS-84)	1F14.4,
	- Observation type	1X,A2,1X
	Set X,Y,Z to zero if not known.	
	Make sure H refers to ITRF or WGS-84!	
	Record required for barometer,	
	recommended for other sensors.	
END OF HEADER	Last record in the header section.	60X

Records marked with * are optional

TABLE A6		
METEOROLOGICAL DATA FILE - DATA RECORD DESCRIPTION		
OBS. RECORD	DESCRIPTION	FORMAT
EPOCH / MET	- Epoch in GPS time (not local time!)	
	year (2 digits, padded with 0 if necessary)	1X,I2.2,
	month,day,hour,min,sec	5(
		1X,I2),
	The 2-digit years in RINEX Version 1 and 2.xx	
	files are understood to represent	
	80-99: 1980-1999 and 00-79: 2000-2079	
	- Met data in the same sequence as given in the	mF7.1
	header	
	More than 8 met data types: Use continuation	
	lines	


```

+-----+-----+-----+-----+-----+-----+-----+-----+
--+
+-----+
---+
|
|                                     TABLE A7
|
|                               GPS OBSERVATION DATA FILE - EXAMPLE
|
+-----+
---+

```

```

----|----1|0---|----2|0---|----3|0---|----4|0---|----5|0---|----6|0---|----7|0---|
--8|

```

```

2.10          OBSERVATION DATA      M (MIXED)          RINEX VERSION /
TYPE
BLANK OR G = GPS, R = GLONASS, E = GALILEO, M = MIXED   COMMENT
XXRINEXO V9.9      AIUB                24-MAR-01 14:43   PGM / RUN BY /
DATE
EXAMPLE OF A MIXED RINEX FILE (NO FEATURES OF V 2.11)  COMMENT
A 9080                                                  MARKER NAME
9080.1.34                                              MARKER NUMBER
BILL SMITH          ABC INSTITUTE                    OBSERVER /
AGENCY
X1234A123          XX                            ZZZ      REC # / TYPE /
VERS
234                YY                            ANT # / TYPE
4375274.          587466.          4589095.          APPROX POSITION
XYZ
.9030            .0000            .0000          ANTENNA: DELTA
H/E/N
1      1
L1/2
1      2      6      G14      G15      G16      G17      G18      G19   WAVELENGTH FACT
L1/2
0
APPL
5      P1      L1      L2      P2      L5          # / TYPES OF
OBSERV
18.000          INTERVAL
2005      3      24      13      10      36.0000000   TIME OF FIRST
OBS
END OF HEADER
05 3 24 13 10 36.0000000 0 4G12G09G06E11
-.123456789
23629347.915          .300 8          -.353      23629364.158
20891534.648          -.120 9          -.358      20891541.292
20607600.189          -.430 9          .394      20607605.848
.324 8
.178 7
05 3 24 13 10 50.0000000 4 4
1      2      2      G 9      G12          WAVELENGTH FACT
*** WAVELENGTH FACTOR CHANGED FOR 2 SATELLITES ***   COMMENT
NOW 8 SATELLITES HAVE WL FACT 1 AND 2!              COMMENT
05 3 24 13 10 54.0000000 0 6G12G09G06R21R22E11
-.123456789
23619095.450          -53875.632 8          -41981.375      23619112.008
20886075.667          -28688.027 9          -22354.535      20886082.101
20611072.689          18247.789 9          14219.770      20611078.410
21345678.576          12345.567 5
22123456.789          23456.789 5
65432.123 5
48861.586 7

```

```

05 3 24 13 11 0.0000000 2 1
*** FROM NOW ON KINEMATIC DATA! *** COMMENT
05 3 24 13 11 48.0000000 0 4G16G12G09G06
-.123456789
21110991.756 16119.980 7 12560.510 21110998.441
23588424.398 -215050.557 6 -167571.734 23588439.570
20869878.790 -113803.187 8 -88677.926 20869884.938
20621643.727 73797.462 7 57505.177 20621649.276
3 4
A 9080 MARKER NAME
9080.1.34 MARKER NUMBER
.9030 .0000 .0000 ANTENNA: DELTA
H/E/N

```

```

--> THIS IS THE START OF A NEW SITE <-- COMMENT
05 3 24 13 12 6.0000000 0 4G16G12G06G09
-.123456987
21112589.384 24515.877 6 19102.763 3 21112596.187
23578228.338 -268624.234 7 -209317.284 4 23578244.398
20625218.088 92581.207 7 72141.846 4 20625223.795
20864539.693 -141858.836 8 -110539.435 5 20864545.943
05 3 24 13 13 1.2345678 5 0
4 1

```

```

(AN EVENT FLAG WITH SIGNIFICANT EPOCH) COMMENT
05 3 24 13 14 12.0000000 0 4G16G12G09G06
-.123456012
21124965.133 89551.30216 69779.62654 21124972.2754
23507272.372 -212616.150 7 -165674.789 5 23507288.421
20828010.354 -333820.093 6 -260119.395 5 20828017.129
20650944.902 227775.130 7 177487.651 4 20650950.363
4 1

```

```

*** ANTISPOOFING ON G 16 AND LOST LOCK COMMENT
05 3 24 13 14 12.0000000 6 2G16G09
123456789.0 -9876543.5
0.0 -0.5
4 2

```

```

---> CYCLE SLIPS THAT HAVE BEEN APPLIED TO COMMENT
THE OBSERVATIONS COMMENT
05 3 24 13 14 48.0000000 0 4G16G12G09G06
-.123456234
21128884.159 110143.144 7 85825.18545 21128890.7764
23487131.045 -318463.297 7 -248152.72824 23487146.149
20817844.743 -387242.571 6 -301747.22925 20817851.322
20658519.895 267583.67817 208507.26234 20658525.869
4 3

```

```

*** SATELLITE G 9 THIS EPOCH ON WLFACT 1 (L2) COMMENT
*** G 6 LOST LOCK AND THIS EPOCH ON WLFACT 2 (L2) COMMENT
(OPPOSITE TO PREVIOUS SETTINGS) COMMENT

```

```

----|----1|0----|----2|0----|----3|0----|----4|0----|----5|0----|----6|0----|----7|0----|
--8|

```

```

+-----+
+-----+
|
|                                     TABLE A8
|
|                                     GPS NAVIGATION MESSAGE FILE - EXAMPLE
|
+-----+
+-----+

```

```

----|----1|0----|----2|0----|----3|0----|----4|0----|----5|0----|----6|0----|----7|0----|
--8|

```

```

2.10 N: GPS NAV DATA RINEX VERSION /
TYPE
XXRINEXN V2.10 AIUB 3-SEP-99 15:22 PGM / RUN BY /

```



```

ROTRONIC          I-240W          5.0    HR SENSOR
MOD/TYPE/ACC
    0.0          0.0          0.0    1234.5678 PR SENSOR POS XYZ/H
                                END OF HEADER
96  4  1  0  0 15  987.1   10.6   89.5
96  4  1  0  0 30  987.2   10.9   90.0
96  4  1  0  0 45  987.1   11.6   89.0

```

```

----|---1|0---|---2|0---|---3|0---|---4|0---|---5|0---|---6|0---|---7|0---|---8|

```

```

+-----+
--+
|                                     TABLE A10
|
|          GLONASS NAVIGATION MESSAGE FILE - HEADER SECTION DESCRIPTION
|
+-----+
--+
|  HEADER LABEL  |  DESCRIPTION  |  FORMAT
|  (Columns 61-80) |              |
|
+-----+
--+
|RINEX VERSION / TYPE| - Format version (2.10) | F9.2,11X,
|                    | - File type ('G' = GLONASS nav mess data) | A1,39X
|
+-----+
--+
|PGM / RUN BY / DATE | - Name of program creating current file | A20,
|                    | - Name of agency creating current file | A20,
|                    | - Date of file creation (dd-mmm-yy hh:mm) | A20
|
+-----+
--+
*|COMMENT          | Comment line(s) | A60
|*
+-----+
--+
*|CORR TO SYSTEM TIME | - Time of reference for system time corr |
|*                  | (year, month, day) | 3I6,
|                    | - Correction to system time scale (sec) |
|3X,D19.12 | to correct GLONASS system time to |
|                    | UTC(SU) (-TauC) | *)
|
+-----+
--+
*|LEAP SECONDS      | Number of leap seconds since 6-Jan-1980 | I6
|*
+-----+
--+
|END OF HEADER      | Last record in the header section. | 60X
|
+-----+
--+

```

Records marked with * are optional

TABLE A11		
GLONASS NAVIGATION MESSAGE FILE - DATA RECORD DESCRIPTION		
OBS. RECORD	DESCRIPTION	FORMAT
PRN / EPOCH / SV CLK	- Satellite number:	I2,
	Slot number in sat. constellation	
	- Epoch of ephemerides (UTC)	
1X,I2.2,	- year (2 digits, padded with 0, if necessary)	
4(1X,I2),	- month,day,hour,minute, - second	F5.1,
	- SV clock bias (sec) (-TauN)	D19.12,
	- SV relative frequency bias (+GammaN)	D19.12,
	- message frame time (tk)	D19.12
	(0 .le. tk .lt. 86400 sec of day UTC)	
		*)
	The 2-digit years in RINEX 1 and 2.xx	
	files are understood to represent	
	80-99: 1980-1999 and 00-79: 2000-2079	
BROADCAST ORBIT - 1	- Satellite position X (km)	
3X,4D19.12	- velocity X dot (km/sec)	
	- X acceleration (km/sec2)	
	- health (0=OK) (Bn)	
BROADCAST ORBIT - 2	- Satellite position Y (km)	
3X,4D19.12	- velocity Y dot (km/sec)	
	- Y acceleration (km/sec2)	
	- frequency number (1-24)	
BROADCAST ORBIT - 3	- Satellite position Z (km)	

```

3X,4D19.12 |
|           | -           velocity Z dot   (km/sec)   |
|           | -           Z acceleration (km/sec2) |
|           | - Age of oper. information (days) (E) |
|-----+-----+-----+-----+-----+-----+-----+-----+
--+
```

*) In order to account for the various compilers, E,e,D, and d are allowed letters between the fraction and exponent of all floating point numbers in the navigation message files. Zero-padded two-digit exponents are required, however.

```

+-----+
---+
|                                     TABLE A12
|                                     GLONASS NAVIGATION MESSAGE FILE - EXAMPLE
|-----+
---+
```

```

----|---1|0---|---2|0---|---3|0---|---4|0---|---5|0---|---6|0---|---7|0---|
--8|
```

```

2.10          GLONASS NAV DATA          RINEX VERSION /
TYPE
ASRINEXG V1.1.0 VM AIUB          19-FEB-98 10:42          PGM / RUN BY /
DATE
STATION ZIMMERWALD          COMMENT
1998      2      16      0.379979610443D-06          CORR TO SYSTEM
TIME
```

END OF HEADER

```

3 98 2 15 0 15 0.0 0.163525342941D-03 0.363797880709D-11
0.108000000000D+05
0.106275903320D+05-0.348924636841D+00 0.931322574615D-09
0.000000000000D+00
-0.944422070313D+04 0.288163375854D+01 0.931322574615D-09
0.210000000000D+02
0.212257280273D+05 0.144599342346D+01-0.186264514923D-08
0.300000000000D+01
4 98 2 15 0 15 0.0 0.179599039257D-03 0.636646291241D-11
0.122400000000D+05
0.562136621094D+04-0.289074897766D+00-0.931322574615D-09
0.000000000000D+00
-0.236819248047D+05 0.102263259888D+01 0.931322574615D-09
0.120000000000D+02
0.762532910156D+04 0.339257907867D+01 0.000000000000D+00
0.300000000000D+01
11 98 2 15 0 15 0.0-0.559808686376D-04-0.272848410532D-11
0.108600000000D+05
-0.350348437500D+04-0.255325126648D+01 0.931322574615D-09
0.000000000000D+00
0.106803754883D+05-0.182923507690D+01 0.000000000000D+00
0.400000000000D+01
0.228762856445D+05 0.447064399719D+00-0.186264514923D-08
0.300000000000D+01
12 98 2 15 0 15 0.0 0.199414789677D-04-0.181898940355D-11
0.108900000000D+05
0.131731816406D+05-0.143945598602D+01 0.372529029846D-08
0.000000000000D+00
0.171148715820D+05-0.118937969208D+01 0.931322574615D-09
0.220000000000D+02
```



```

24922041.288      -83151.666 5
22201767.457      -11388.909 5
23734633.024      163360.131 5
23819848.894      -85881.102 5

```

```

----|----1|0----|----2|0----|----3|0----|----4|0----|----5|0----|----6|0----|----7|0----|
--8|

```

```

+-----+
|-----+
|                                     TABLE A14
|                                     MIXED GPS/GLONASS OBSERVATION FILE - EXAMPLE
|-----+
+-----+

```

```

----|----1|0----|----2|0----|----3|0----|----4|0----|----5|0----|----6|0----|----7|0----|
--8|

```

```

      2.10          OBSERVATION DATA      M (MIXED)          RINEX VERSION /
TYPE
YYRINEXO V2.8.1 VM AIUB          6-FEB-00 13:59          PGM / RUN BY /
DATE
TST2          MARKER NAME
001-02-A      MARKER NUMBER
JIM          Y-COMPANY          OBSERVER /
AGENCY
1          YY-RECEIVER          2.0.1          REC # / TYPE /
VERS
1          GEODETIC L1          ANT # / TYPE
      3851178.1849  -80151.4072  5066671.1013  APPROX POSITION
XYZ
      1.2340          0.0000          0.0000          ANTENNA: DELTA
H/E/N
      1          0          WAVELENGTH FACT
L1/2
      2          C1          L1          # / TYPES OF
OBSERV
      10.000          INTERVAL
      11          LEAP SECONDS
      2000          2          6          11          53          0.0000000          GPS          TIME OF FIRST
OBS
          END OF HEADER
00 2 6 11 53 0.0000000 0 14G23G07G02G05G26G09G21R20R19R12R02R11
          R10R03
22576523.586  -11256947.60212
22360162.704  -16225110.75413
24484865.974   14662682.882 2
21950524.331  -13784707.24912
22507304.252   9846064.848 2
20148742.213  -20988953.712 4
22800149.591  -16650822.70012
19811403.273  -25116169.741 3
23046997.513  -3264701.688 2
22778170.622  -821857836.745 1
22221283.991  -988088156.884 2
19300913.475  -83282658.19013
20309075.579  -672668843.84713
23397403.484  -285457101.34211
00 2 6 11 53 10.0000000 0 14G23G07G02G05G26G09G21R20R19R12R02R11
          R10R03
22578985.016  -11244012.910 2
22359738.890  -16227337.841 2
24490324.818   14691368.710 2
21944376.706  -13817012.849 2

```


T	Reference time for polynomial (Seconds into GPS week)	I7,
W	Reference week number (GPS week, continuous number)	I5,
S	EGNOS, WAAS, or MSAS ... (left-justified) Derived from MT17 service provider. If not known: Use Snn with nn = PRN-100 of satellite broadcasting the MT12	X,A5,X
U	UTC Identifier (0 if unknown) 1=UTC(NIST), 2=UTC(USNO), 3=UTC(SU), 4=UTC(BIPM), 5=UTC(Europe Lab), 6=UTC(CRL), >6 = reserved for future Omit record if corrections not provided. Replaces CORR TO SYSTEM TIME !	I2,2X
-----+-----+-----		
* LEAP SECONDS	Number of leap seconds since 6-Jan-1980	I6
-----+-----+-----		
END OF HEADER	Last record in the header section.	60X
-----+-----+-----		

Records marked with * are optional

TABLE A16		
GEOSTATIONARY NAVIGATION MESSAGE FILE - DATA RECORD DESCRIPTION		
OBS. RECORD	DESCRIPTION	FORMAT
PRN / EPOCH / SV CLK	- Satellite number (PRN - 100)	I2,
	- Epoch of ephemerides (GPS) (Toe)	
	- year (2 digits, padded with 0	

		if necessary)	
1X,I2.2,		- month,day,hour,minute,	
4(1X,I2),		- second	F5.1,
		- SV clock bias (sec)	(aGf0) D19.12,
		- SV relative frequency bias	(aGf1) D19.12,
		- Transmission time of message	D19.12
		(start of the message)	
		in GPS seconds of the week	

-----+			
3X,4D19.12	BROADCAST ORBIT - 1	- Satellite position X	(km)
		- velocity X dot	(km/sec)
		- X acceleration	(km/sec2) *)
		- health (0=OK)	

-----+			
3X,4D19.12	BROADCAST ORBIT - 2	- Satellite position Y	(km)
		- velocity Y dot	(km/sec)
		- Y acceleration	(km/sec2)
		- Accuracy code	(URA, meters)

-----+			
3X,4D19.12	BROADCAST ORBIT - 3	- Satellite position Z	(km)
		- velocity Z dot	(km/sec)
		- Z acceleration	(km/sec2)
		- IODN (Issue of Data Navigation, DO229,	
		8 first bits after Message Type if MT9)	

-----+

*) In order to account for the various compilers, E,e,D, and d are allowed letters between the fraction and exponent of all floating point numbers in the navigation message files. Zero-padded two-digit exponents are required, however.

----|---1|0---|---2|0---|---3|0---|---4|0---|---5|0---|---6|0---|---7|0---|---8|

2.10 OBSERVATION DATA M (MIXED) RINEX VERSION /
TYPE
RinExp V.2.0.2 TESTUSER 00-02-04 09:30 PGM / RUN BY /
DATE
COMMENT
The file contains L1 pseudorange and phase data of the
geostationary AOR-E satellite (PRN 120 = S20)
COMMENT
COMMENT
COMMENT
TLSE D MARKER NAME
ESTB TESTAGENCY OBSERVER /
AGENCY
SGL98030069 Novatel Millennium HW3-1 SW 4.45/2.3 REC # / TYPE /
VERS ASH701073.1 ANT # / TYPE
4629365.0750 112100.1790 4371619.4160 APPROX POSITION
XYZ 0.0000 0.0000 0.0000 ANTENNA: DELTA
H/E/N 1 1 WAVELENGTH FACT
L1/2 4 C1 L1 L2 P2 # / TYPES OF
OBSERV 1 INTERVAL
2000 1 13 14 45 0.000000 GPS TIME OF FIRST
OBS 2000 1 13 15 0 0.000000 GPS TIME OF LAST OBS
0 RCV CLOCK OFFS
APPL END OF HEADER

00 01 13 14 45 0.0000000 0 8G25G17G06G05G24G29G30S20
0.000535140
21839900.207 -236148.877 9 -184047.71049 21839901.4384
25151926.413 -161002.900 9 -125509.72447 25151935.8274
20531103.515 763336.059 9 594797.53149 20531105.0114
23001624.801 -432989.642 9 -337436.50348 23001628.1684
23610349.510 -384890.728 9 -299952.38848 23610354.3504
23954474.398 -151982.173 9 -118480.96847 23954481.1994
20622367.016 -332628.466 9 -259214.55249 20622367.8754
38137559.506 335849.135 9
00 01 13 14 45 1.0000000 0 8G25G17G06G05G24G29G30S20
0.000535144
21839500.278 -238250.743 9 -185685.52549 21839501.4814
25151246.148 -164576.503 9 -128294.33947 25151256.2614
20531084.382 763235.849 9 594719.44849 20531085.8784
23002123.430 -430369.237 9 -335394.62748 23002126.7114
23610670.127 -383205.864 9 -298639.51048 23610674.9834
23955051.773 -148948.417 9 -116117.00748 23955058.5034
20622558.579 -331621.765 9 -258430.11049 20622559.4574
38137558.783 335846.284 9
00 01 13 14 45 2.0000000 0 8G25G17G06G05G24G29G30S20
0.000535144
21839100.418 -240352.173 9 -187323.00449 21839101.6534
25150565.890 -168150.148 9 -131078.97647 25150576.2144
20531065.378 763136.116 9 594641.73549 20531066.8984
23002622.082 -427748.683 9 -333352.63648 23002625.3444
23610990.819 -381520.461 9 -297326.20848 23610995.8424
23955629.062 -145914.531 9 -113752.94748 23955636.5544
20622750.161 -330614.723 9 -257645.40149 20622751.0554
38137558.365 335843.457 9

----|---1|0---|---2|0---|---3|0---|---4|0---|---5|0---|---6|0---|---7|0---|---8|

```

+-----+
---+
|
|                                     TABLE A18
|
|                               GEO NAVIGATION MESSAGE FILE - EXAMPLE
|
+-----+

```

```

---+
----|---1|0---|---2|0---|---3|0---|---4|0---|---5|0---|---6|0---|---7|0---|-
--8|

```

```

2.11          H: GEO NAV MSG DATA          RINEX VERSION /
TYPE
SBAS2RINEX 2.0      CNES          20-Oct-03 14:01      PGM / RUN BY /
DATE
0.133179128170D-06-0.107469588780D-12 518400 1240 EGNOS 5 D-UTC
A0,A1,T,W,S,U
13
This file contains navigation message data from a SBAS      LEAP SECONDS
(geostationary) satellite, here AOR-W (PRN 122 = # 22)      COMMENT
                                                                COMMENT
                                                                END OF HEADER

```

```

22 03 10 18 0 1 4.0-1.005828380585D-07 6.366462912410D-12
5.184420000000D+05
2.482832392000D+04-3.593750000000D-04-1.375000000000D-07
0.000000000000D+00
-3.408920872000D+04-1.480625000000D-03-5.000000000000D-08
4.000000000000D+00
-1.650560000000D+01 8.360000000000D-04 6.250000000000D-08
2.300000000000D+01
22 03 10 18 0 5 20.0-9.872019290924D-08 5.456968210638D-12
5.186940000000D+05
2.482822744000D+04-3.962500000000D-04-1.375000000000D-07
0.000000000000D+00
-3.408958936000D+04-1.492500000000D-03-5.000000000000D-08
4.000000000000D+00
-1.628960000000D+01 8.520000000000D-04 6.250000000000D-08
2.400000000000D+01
22 03 10 18 0 9 36.0-9.732320904732D-08 4.547473508865D-12
5.189510000000D+05
2.482812152000D+04-4.325000000000D-04-1.375000000000D-07
0.000000000000D+00
-3.408997304000D+04-1.505000000000D-03-5.000000000000D-08
4.000000000000D+00
-1.606960000000D+01 8.800000000000D-04 6.250000000000D-08
2.500000000000D+01
22 03 10 18 0 13 52.0-9.592622518539D-08 4.547473508865D-12
5.192110000000D+05
2.482800632000D+04-4.681250000000D-04-1.375000000000D-07
0.000000000000D+00
-3.409035992000D+04-1.518125000000D-03-3.750000000000D-08
4.000000000000D+00
-1.584240000000D+01 8.960000000000D-04 6.250000000000D-08
2.600000000000D+01

```

```

----|---1|0---|---2|0---|---3|0---|---4|0---|---5|0---|---6|0---|---7|0---|-
--8|

```